



SQUARE DRAWN STEEL S235JRC, C45 acc. to EN 10277-2

Pręty ciągnięte na zimno kwadratowe w gatunku S235JRC
oraz C45 zgodnie z EN 10277-2

size mm	weight kg/m
8	0,502
9	0,636
10	0,785
12	1,13
13	1,33
14	1,54
15	1,77
16	2,01
18	2,54
20	3,14
22	3,80
24	4,52
25	4,91
26	5,26
28	6,10
30	7,06
32	8,04
35	9,62
40	12,60
45	15,90
50	19,60
55	23,70
60	28,30
70	38,50
80	50,20
90	63,59
100	78,50

TOLERANCES FLAT DRAWN STEEL EN 10278

Tolerancje wymiarowe dla płaskowników zgodnie z EN 10278

width mm	tolerance		
	mm	mm	ISO
up to 6	+0	-0,075	h11
over 6 up to 10	+0	-0,09	h11
over 10 up to 18	+0	-0,11	h11
over 18 up to 30	+0	-0,13	h11
over 30 up to 50	+0	-0,16	h11
over 50 up to 80	+0	-0,19	h11
over 80 up to 100	+0	-0,22	h11
over 100 up to 150	+0,50	-0,50	
over 150 up to 200	+1,00	-1,00	
over 200 up to 300	+2,00	-2,00	
over 300 up to 400	+2,50	-2,50	